



www.kmsavotec.com

KW500 SIMPLY

RACCOGLICAVO



Il raccogli cavo **KW500-SIMPLY** è utilizzato per la creazione di matasse di cavo. È una macchina semiautomatica che va collegata alle tagliaspela KM SAVOTEC e necessita la presenza dell'operatore, per il prelievo della matassa. La macchina collegata direttamente alla tagliaspela inizia la rotazione contemporaneamente alla macchina mentre trascina il cavo stesso. La velocità di avvolgimento si autoregola in base alla velocità di trasporto cavo impostato sulla tagliaspela.

La matassa si crea mediante avvolgimento del cavo sui pioli stessi, i quali possono essere regolati da un diametro interno minimo di 120 mm a massimo di 300 mm. L'interfaccia utente facile ed intuitiva fornita dal display touch screen permette l'impostazione di tutti i dati necessari alla gestione della macchina, comprensiva di pagina della diagnostica macchina, pagina di selezione lingue, ecc

KW500 SIMPLY

PESO - WEIGHT	90 KG.
DIMENSION I- DIMENSION	1100 x 950 x 1500
ALIMENTAZIONE - POWER SUPPLY	230V 50-60HZ MONOFASE - 1 PHASE
ASSORBIMENTO - POWER CONSUMPTION	2.0 Kw
DIAMETRO ESTERNO CAVO MIN. MINIMUM EXTERNAL CABLE DIAMETER	1,00 mm
DIAMETRO ESTERNO CAVO MAX MAXIMUM EXTERNAL CABLE DIAMETER	15,00 mm
PRESSIONE ARIA - AIR PRESSURE	6 bar



www.kmsavotec.com

KW500 SIMPLY

CABLE COLLECTOR



The **KW500-SIMPLY** cable collector is used for the creation of cable coils, it is a semi-automatic machine that must be connected to the KM SAVOTEC cut-stripping machine. It requires the presence of the operator to pick up the skein. The machine connected directly to the cut-stripping machine starts the rotation at the same time as the stripping machine, while dragging the cable itself. The winding speed adjusts itself according to the cable transport speed set on the stripping cutter. The coil

is created by winding the cable on the pegs themselves, which can be adjusted from an internal diameter of 120 mm to a maximum of 300 mm. The easy and intuitive user interface, provided by the touch screen display allows to set up all the data needed to manage the machine, including machine diagnostics page, language selection page, etc.

KW500 SIMPLY

PESO - WEIGHT	90 KG.
DIMENSION I- DIMENSION	1100 x 950 x 1500
ALIMENTAZIONE - POWER SUPPLY	230V 50-60HZ MONOFASE - 1 PHASE
ASSORBIMENTO - POWER CONSUMPTION	2.0 Kw
DIAMETRO ESTERNO CAVO MIN. MINIMUM EXTERNAL CABLE DIAMETER	1,00 mm
DIAMETRO ESTERNO CAVO MAX MAXIMUM EXTERNAL CABLE DIAMETER	15,00 mm
PRESSIONE ARIA - AIR PRESSURE	6 bar

All data and measures are indicative and can be changed without notice. Certain types of extremely hard, tough wires may not be able to be processed even if written within the indicated ranges. In case of doubt, KM Savotec is willing to produce samples of your wire.