



LC 3000 SPECIAL

9 METER VERSION



Il raccogli cavo lineare della serie **LC Series** è utilizzato per la raccolta dei cavi provenienti dalle macchine taglia spela. Il raccogli cavo può avere un funzionamento autonomo o con interfacciamento elettrico con la macchina taglia spela, questo consente di collegare il raccogli cavo LC Series a tutte le macchine taglia spela, sia quelle elettroniche di nuova generazione sia quelle elettropneumatiche. La macchina è dotata di serie della doppia bacinella per la separazione dei lotti e di un nastro trasportatore.

Ogni cavo processato, viene preso da alcune pinze presenti nel canale di convogliamento cavo che permettono di scaricare i cavi uno ad uno nella prima bacinella

di raccolta con alta precisione di posizionamento tra un cavo e l'altro. L'interfaccia utente fornita dal display touch screen tramite una interfaccia facile e intuitiva permette l'impostazione di tutti i dati per la gestione della macchina, impostazione pezzi, pulsante di avvenuto scarico, impostazione velocità nastro trasportatore, selezione dei tempi per lo scarico cavi, pagina della diagnostica macchina, pagina di selezione lingue, ecc. La versione speciale prevede l'aggiunta di due prolunghe da 3 metri per un totale di lunghezza del raccogli cavo di 9 metri. Tramite il software touchscreen possono essere abilitate e disabilitate le prolunghe in caso di non utilizzo, per alcuni tipi di lavorazioni.

LC 3000 Special

PESO - WEIGHT

250 KG. EACH MODULE

ALIMENTAZIONE - POWER SUPPLY

230V 50-60HZ
MONOFASE - 1 PHASE

ASSORBIMENTO - POWER CONSUMPTION

1.5 Kw

DIAMETRO ESTERNO CAVO MINIMO
MINIMUM EXTERNAL CABLE DIAMETER

1,00 mm

DIAMETRO ESTERNO CAVO MASSIMO
MAXIMUM EXTERNAL CABLE DIAMETER

14,00 mm

PRESSIONE ARIA - AIR PRESSURE

6 bar.



LC 3000 SPECIAL

9 METER VERSION



The linear cable collector of the **LC Series** is used to collect the cables coming from the stripping and crimping machines. The cable collector can operate independently or with electrical interface with the machine cut off, this allows you to connect the cable collector LC Series to all machines cut off, both electronic new generation and electropneumatic.

The machine is equipped with a standard double tray for the separation of batches and a conveyor belt. Each cable processed, is taken from some pliers present in the cable conveying channel that allow you to unload the cables one by one in the first collection basin with

high positioning accuracy between one cable and the other. The user interface provided by the touch screen display through an easy and intuitive interface allows the setting of all data for machine management, part setting, button unloading, belt speed setting, Time selection for cable unloading, machine diagnostics page, language selection page, etc. The special version includes the addition of two extensions of 3 meters for a total length of the cable collector of 9 meters. With the touchscreen software, extensions can be enabled and disabled in case of non-use, for certain types of processing.

LC 3000 Special

PESO - WEIGHT

250 KG. EACH MODULE

ALIMENTAZIONE - POWER SUPPLY

230V 50-60HZ
MONOFASE - 1 PHASE

ASSORBIMENTO - POWER CONSUMPTION

1.5 Kw

DIAMETRO ESTERNO CAVO MINIMO
MINIMUM EXTERNAL CABLE DIAMETER

1,00 mm

DIAMETRO ESTERNO CAVO MASSIMO
MAXIMUM EXTERNAL CABLE DIAMETER

14,00 mm

PRESSIONE ARIA - AIR PRESSURE

6 bar.